REPORT DOCUMENTATION PAGE

Form Approved OMB NO. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggesstions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any oenalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

I LEAGE DO IN	OT INCTOININ TOOL	CI ORIWI TO THE	ADOVE ADDITESS.				
1. REPORT DATE (DD-MM-YYYY)			2. REPORT TYPE		3. DATES COVERED (From - To)		
17-08-2015			Conference Proceeding		-		
4. TITLE A	. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Frequency Conversion of Short Optical Pulses inNegatively Spatially Dispersive Metamaterials				W911	W911NF-14-1-0619		
				5b. GRANT NUMBER			
				5c. PR	5c. PROGRAM ELEMENT NUMBER		
				611102			
6. AUTHOR	RS			5d. PR	5d. PROJECT NUMBER		
Alexander K. Popov, Sergey A. Myslivets							
				5e. TA	SK NUMBER		
				5f. WC	ORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES Purdue University Young Hall 155 South Grant Street					8. PERFORMING ORGANIZATION REPORT NUMBER		
West Lafay	ette, IN	4790	07 -2114				
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES)					10. SPONSOR/MONITOR'S ACRONYM(S) ARO		
U.S. Army Research Office P.O. Box 12211					11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
Research Triangle Park, NC 27709-2211					65605-PH.8		
12. DISTRIBUTION AVAILIBILITY STATEMENT					03003-111.0		
	r public release; o		ilimitea.				
The views, o		ndings contained	I in this report are those of the second second the second		nd should not contrued as an official Department		
	hat particular s		utions of nanoscopic pl ncy-shifted reflectivity		lding blocks in metamaterials may enable naping.		
15. SUBJEO	CT TERMS ptics, materials, h	armonic general	tion and mixing				
16. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE ABSTRACT				15. NUMB OF PAGES	ER 19a. NAME OF RESPONSIBLE PERSON Alexander Popov		
UU LEPORT		UU PAGE	UU	111020	19b. TELEPHONE NUMBER 920-205-7474		
	<u> </u>				720-203-7474		

Report Title

Frequency Conversion of Short Optical Pulses in Negatively Spatially Dispersive Metamaterials

ABSTRACT

We show that particular spatial distributions of nanoscopic plasmonic building blocks in metamaterials may enable extraordinary nonlinear-optical frequency-shifted reflectivity and pulse shaping.

Conference Name: Frontiers in Optics: The 99th OSA Annual Meeting and Exhibit/Laser Science XXXI

Conference Date: October 18, 2015

Frequency Conversion of Short Optical Pulses in Negatively Spatially Dispersive Metamaterials

A. K. Popov ¹ and S. A. Myslivets ^{2,3}

Birck Nanotechnology Center, Purdue University, West Lafayette, IN 47907, USA
 Institute of Physics, Siberian Branch of the Russian Academy of Sciences, 660036 Krasnoyarsk, Russian Federation
 Siberian Federal University, 660041 Krasnoyarsk, Russian Federation

popov@purdue.edu; sam@iph.krasn.ru

Abstract: We show that particular spatial distributions of nanoscopic plasmonic building blocks in metamaterials may enable extraordinary nonlinear-optical frequency-shifted reflectivity and pulse shaping.

© 2015 Optical Society of America

OCIS codes: 190.4400 (Nonlinear optics, materials), 190.2620 (Harmonic generation and mixing).

Metamaterials (MM) are artificially designed and engineered materials, which can have properties unattainable in nature. Usually, MM rely on advances in nanotechnology to build tiny metallic nanostructures smaller than the wavelength of light. These nanostructures modify the electromagnetic (EM) properties of MM, sometimes creating seemingly impossible optical effects. Negative-index MM (NIMs) are most intriguing EM materials that support backward EM waves (BEMW). Phase velocity and energy flux (group velocity) become *contra-directed* in NIMs. The appearance of BEMW is commonly associated with simultaneously negative electric permittivity ($\varepsilon < 0$) and magnetic permeability ($\mu < 0$) at corresponding frequencies and, consequently, with negative refractive index $n = -\sqrt{\mu\varepsilon}$. Counter-intuitive backwardness of EMW is in strict contrast with the electrodynamics of ordinary, positive-index materials. The possibility of huge enhancement of optical parametric amplification has been predicted through three-wave mixing in NIMs if one of the coupled electromagnetic waves falls in the negative-index frequency domain [1,2]. Unparalleled properties of second harmonic generation in NIMs were predicted in [2,3]. It was shown that frequency-mixing of ordinary and BEMV enables frequency shifted amplified reflection of electromagnetic waves [4].

Current mainstream in fabricating bulk NIM slabs relies on engineering of LC nanocircuits - plasmonic mesoatoms with negative electromagnetic response. Extraordinary coherent nonlinear optical frequency-converting propagation processes predicted in NIMs have been realized (simulated) so far only in the microwave transmission lines [5]. This paper proposes a different paradigm which employs spatial dispersion [6] to realize outlined processes. We show that metamaterial slabs which may support coexistence of ordinary electromagnetic waves with co-directed phase velocity and energy flux $(\partial \omega/\partial k > 0)$ and extraordinary optical modes with contra-directed phase and group velocities $(\partial \omega/\partial k < 0)$ enable extraordinary nonlinear optical processes similar to that predicted in NIMs. Particularly, the focus is on the extraordinary properties of nonlinear optical frequency-mixing of contra-propagating ordinary short optical pulses and pulses with negative group velocity which have been studied through numerical simulations.

One of the possible realization of the outlined approach is a plasmonic metaslab made of carbon nanotubes. It can be viewed as a plasmonic wave guide formed by a metal plate (bottom) and by air (top) tampered by standing carbon nanotubes [7]. Such a structure supports different EM eigenmodes in the THz and mid IR. Some of them exhibit spatial dispersion which changes from positive to negative in different wavelength intervals whereas others predominantly maintain negative dispersion. Frequencies and gaps between the modes can be tailored by changing lengths and spacing between the nanotubes so that phase velocities for the modes matching the photon energy conservation law would become equal as their group velocities remain contra-directed. Basically, different materials and geometries can be utilized to control spatial dispersion and losses in such MM with variable spatial dispersion [8].

Unparalleled properties of nonlinear-optical coupling (collision) of short contra-propagating pulses in such MMs are illustrated in Fig. 1 (a) – (d) for the example of BW second harmonic (SH) generation in the loss-free MM. Here τ is the time interval measured in units of the input pulse duration [Figs. 1 (a), (b)]. Position of the fundamental and SH pulses inside the metaslab is measured in units of the input pulse length l [Figs. 1 (c), (d)]. Second harmonic is generated only inside the fundamental pulse. It travels in the opposite direction and exits from the fundamental pulse. This results in different durations of the fundamental and SH pulses exiting from the opposite sides of the




Fig. 1. Phase-matched backward-wave SH generation in the loss-free MM. (a) and (c): Input rectangular $T_1(z=0)$ and output $T_1(z=L)$ pulse shapes for the fundamental radiation; $\eta_2(z=0)$ are pulse shapes for the emitted back second harmonic. (b) and (d): Change of the pulse energy at the corresponding frequencies across the slab. Here, d = L/l, $2S_2/S_{10}$ is photon conversion efficiency. $\alpha_{1,2}$ and g are absorption and nonlinear coupling parameters.

metaslab. The metaslab operates as controlled frequency doubling microscopic nonlinear-optical metamirror. Shapes of the output transmitted and generated SH pulses depend on the energy conversion rate inside the fundamental pulse and, hence, can be controlled by changing intensity and ratio of the the input pulse length to the metamaterial thickness (parameter d). It is demonstrated in Figs. 1 (a), (b). Figures 1 (c), (d) display overall pulse energy (photon) conversion efficiency across the metaslab. Unusual behavior is due to the opposite propagation direction of the pulses.

In the conclusion, we show that a deliberately engineered highly dispersive metamaterial slab enables switching of optical pulses to contra-propagated frequency shifted pulses with tailored pulse shape. Enhanced efficiency of switching is ensured by the extraordinary phase matching of contra-propagating light pulses. Extraordinary properties of coherent nonlinear-optical switching in short-pulse regime in such metamaterials are demonstrated through numerical simulations. It is shown that greatly enhanced nonlinear optical coupling and frequency conversion become possible due to extraordinary opposite directions of phase and group velocities for one of the pulses, whereas other coupled pulses remain ordinary. Then the metaslab operates as a *frequency-converting nonlinear-optical microscopic metamir-ror and switch*. Other prospective applications in the photonic device technologies will be discussed.

Acknowlwdgement This work was supported in parts by the NSF (Grant ECCS-1346547), by the AFOSR (Grant FA950-12-1-298), by the ARO (Grant W911NF-14-1-0619) and by the Russian Foundation for Basic Research (Grant RFBR 15-02-03959A). The authors thank I. S. Nefedov for inspiring inputs.

References

- 1. A. K. Popov and V. M. Shalaev, "Compensating losses in negative-index metamaterials by optical parametric amplification," Opt. Lett. **31**, 2169–2171 (2006).
- 2. A. K. Popov and V. M. Shalaev, "Negative-index metamaterials: second harmonic generation, ManleyRowe relations and parametric amplification," Appl. Phys. B Lasers Opt. **84**, 131-137 (2006).
- 3. I. V. Shadrivov, A. A. Zharov, and Yu. S. Kivshar, "Second-harmonic generation in nonlinear left-handed metamaterials," J. Opt. Soc. Am. B23, 529–534 (2006).
- 4. A. K. Popov and S. A. Myslivets, "Nonlinear-optical metamirror," Appl. Phys. A 103, 725-729 (2011).
- 5. A. Rose, Da Huang and D. R. Smith, "Controlling the second harmonic in a phase-matched negative-index metamaterial," Phys. Rev. Lett. **107**, 063902-4 (2011).
- 6. V. M. Agranovich, Yu. N. Gartstein, "Spatial dispersion and negative refraction of light," Physics-Uspekhi (UFN) **176**, 10511068 (2006).
- 7. I. Nefedov and S. Tretyakov, "Ultrabroadband electromagnetically indefinite medium formed by aligned carbon nanotubes," Phys. Rev. **B 84**, 113410-4 (2011).
- 8. E. E. Narimanov, "Photonic hypercrystal," Phys. Rev. X 4, 041014 (2014).